

## MBI's Most Powerful Shear Range Ever!

INMALO are pleased to introduce the new MBI EAGLE III Shears which provide a host of upgrades and will run alongside the well-proven Eagle II series. The new range of Eagle Shears is designed to be a market leader for power and reliability competing against the biggest names in the industry with larger cylinders offering 25-30% more power, as well as redesigned seals that can work at 380 bar pressure.

These shears are designed to take on the most demanding projects with upgraded wear parts and an improved jaw. Now there is no other choice for productivity and value for money over the lifetime of the attachment.

CALL & BOOK YOUR DEMO NOW!

01962 760055

- Increased working pressure to 380 bar. 25-30% extra power
- Improved cutting and reduced maintenance with new piercing tip
- Improved productivity and reduced down-time
- Main sections are cut from a single piece of steel increasing strength
- Shorter body improving weight distribution
- Cut your scrap processing cost
- All scrap shears and spares stored in our UK depot
- Experienced engineers to provide back-up
  & service support









## Eagle III Scrap Shears





## MBI Eagle III SH Scrap Shear Range

Reliability and productivity are key words of the MBI range of hydraulic attachments and a number of improvements have been made including an improved piercing tip that is stronger and covers the end of the beak to reduce rebuilding works and Hardox 500 plates have been fitted to the jaw, again to reduce downtime.

To improve material quality the jaws are built from single sections of steel which has reduced the number of welding joints and improved tool strength.

The Eagle III range covers machines from 20t to 150t. The SH800 (8,000kg) and SH15000 (15,000kg) have completed well over 4,000 hours of work in the field on test with incredible results and minimal down-time.

SPARES ARE ALSO AT A REASONABLE PRICE KEEPING YOUR LIFETIME OWNERSHIP COSTS DOWN



CLICK to watch the power for yourself













TECHNICAL SPECIFICATION							
Model	SH250R	SH320R	SH490R	SH600R	SH800R	SH1500R	SH2200R
Weight (with bracket)	2,600kg	3,300kg	5,150kg	6,360kg	8,700kg	15,000kg	22,000kg
Jaw Opening	530mm	620mm	730mm	780mm	900mm	1,100mm	1,250mm
Jaw Depth	570mm	640mm	760mm	800mm	890mm	1,100mm	1,290mm
Length	2,700mm	2,975mm	3,450mm	3,710mm	3,980mm	4,800mm	5,550mm
Excavator Weight Dipper Mount	24-29t	30-40t	45-55t	55-65t	75-85t	120-170t	170-300t
Excavator Weight Boom Mount	17-19t	20-28t	28-39t	39-45t	45-60t	80-110t	110-160t
Oil Flow O/C (L/min)	200-250	250-300	300-350	500-600	600-700	800-1,000	800-1,000
Presure O/C (Bar)	320-380	320-380	320-380	320-380	320-380	320-380	320-350