




# RP-IT

## ROTATING PULVERISER





The RP-IT has become a benchmark in the demolition industry due to its power, robustness & ease of maintenance. It is suitable for both primary and secondary demolition, also on high reach applications.

- The reinforced RP-IT structure is designed to last forever and facilitates the crushed material falling through the jaw.
- The continuous hydraulic rotation enables precise positioning during in height demolitions and ground operations, while its robust components grant high durability.



- **Split Top Jaw Plates** - As the front plate always wears before the rear, you can replace only this part saving you time and money on maintenance costs.



- The interchangeable parts, like teeth plates and blades, ensure quick and easy maintenance.

### TECHNICAL DATA

BT.RP-IT.10

MODEL		RP10-IT	RP16-IT	RP20-IT	RP30-IT	RP40-IT	RP50-IT	RP80-IT
ROTATION		360° Hydraulic						
EXCAVATOR WEIGHT	t	10-15	16-20	21-26	27-35	35-50	50-65	70-95
TOOL WEIGHT *	kg	1100	1690	2000	2850	4100	5200	8200
OPENING	mm	580	700	750	900	1000	1100	1250
HEIGHT MAX.	mm	1710	2150	2130	2400	2780	3000	3600
HYDRAULIC WORKING PRESSURE	bar	300-350	300-350	300-350	300-350	300-350	300-350	300-350
OIL FLOW	l/min	100-180	130-150	180-200	200-220	220-280	335-375	500-600



- **Speed-Valve**  
The speed valve reduces opening and closing time boosting productivity.

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice.  
\* Tool weight does include Mantovanibenne top bracket.